

At the heart of the FirePro® Xtinguish system is the HCVR-3 Conventional Releasing Fire Alarm Control Panel. The HCVR-3 monitors and controls the entire system; detection, annunciation, and suppression. Combined with Hochiki's high-quality detectors and FirePro® Xtinguish, the HCVR-3 is a perfect solution for all of your fire suppression needs.



## HCVR-3

### CONVENTIONAL RELEASING FIRE ALARM CONTROL PANEL

- UL Listed, FM Approved and CSFM listed
- Three conventional zones
- Any single zone or any combination of zones can be configured to release
- Fully programmable using simple menu options
- Simple, single board construction
- Installer-friendly
- Compatible with a wide range of detection devices
- Configurable first stage NAC delays
- Configurable detection delays
- Built-in manual release switch and external manual release circuit
- Built-in abort circuit
- Compatible with FirePro® Xtinguish
- Compatible with various releasing valves
- Configurable releasing delays up to 60 seconds in 5-second intervals
- Configurable releasing duration up to 5 minutes in 5-second intervals
- Releasing countdown timer displayed on the panel
- Supports up to seven HCVR-SDU or HCVR-AB
- Built-in relays for Fire, Trouble, Stage 1, Stage 2, Extract and Local Fire
- Available in red or gray



## HCVR-SDU

### STATUS DISPLAY UNIT

- Remote status display for the HCVR-3 Releasing FACP
- UL Listed, FM Approved and CSFM listed
- Supervised four-wire connection
- Displays countdown timer prior to agent release
- Internal buzzer and trouble diagnosis indicators
- Optional keyswitch with Manual-Only and Automatic & Manual modes
- Available in red or gray



## HCVR-AB

### ANCILLARY BOARD

- Provides additional normally open contacts which mimic the outputs of the HCVR-3 Releasing FACP
- Requires data cable and 24VDC connections
- Up to 7 HCVR-AB can be connected to a single HCVR-3 Releasing FACP
- Includes a back box for surface mount (except board only model)
- UL Listed, FM Approved and CSFM listed

# X T I N G U I S H



## HCVR-AS ABORT SWITCH

- UL Listed, FM Approved and CSFM listed
- Used to abort the releasing operation
- Includes a back box for surface mount
- Available in red or gray



## HCVR-DS DISCONNECT SWITCH

- UL Listed, FM Approved and CSFM listed
- Physical switch provides NFPA-compliant disconnect solution for releasing service
- Includes a back box for surface mount
- Available in red or gray



## HCVR-SQA SEQUENTIAL ACTIVATOR

- UL Listed, FM Approved and CSFM listed
  - Used to activate up to two FirePro® Xtinguish aerosol generators
  - Includes a back box for surface mount
  - Fault LED is illuminated to indicate trouble conditions
- \*Maximum 20 HCVR-SQA modules and 40 generators per control panel.



## HPS-DAK-SR MANUAL PULL STATION FOR FIRE SUPPRESSION RELEASE

- Metal construction
- Enclosed switch with glass rod (included)
- UL Listed, CSFM listed